

# EPROG1350M

## Eco Pro 1350 Litre Upright Meat/Chill Cabinet



### Temperature


---



Meat-Chill  
-2/2 C

### Dimensions (mm)

---



### Capacity

---

1350 Litres

### Features & Benefits

---

Providing excellence and practicality at a very competitive price, the Eco Pro range generates significant energy and carbon reductions in use saving you money on your operating costs whilst at the same time never compromising on your commitment to food safety

- Smart Controller reduces energy consumption by up to 20%
- Energy-saving Hydrocarbon refrigerant option (available at no extra cost) offers up to 15% saving on running costs
- Concealed fan and evaporator for improved safety and more usable space
- Energy-saving Hydrocarbon refrigerant option offers up to 15% saving on running costs

- Energy Efficient self closing doors with durable steel hinges

Supplied as Standard     Optional     Not Available     Yes     No

### External Finish

---

304 Stainless Steel   

Stainless Steel   

304 Stainless Steel Rear For Island Siting   

### Internal Finish

---

304 Stainless Steel   

Aluminium   

### Shelving

---

Nylon Coated Gastronorm 2/1 Shelf        Quantity: 6

Additional Shelf   

### Doors

---

Solid Full   

Solid Half   

### Base Fittings

---

80mm Castors   

150mm Legs   

### Refrigeration

---

Forced Air	<input checked="" type="radio"/>
Integral	<input checked="" type="radio"/>
Remote - less condensing unit	<input type="radio"/>
R290 (Hydrocarbon)	<input type="radio"/>
R134a	<input checked="" type="radio"/>
Thermal Heat Rejection (Kw/24hrs)	<input type="radio"/>
Noise DBA	<input type="radio"/>
Drain Required?	<input checked="" type="radio"/>

### Electrical Data

---

230 Volts	<input checked="" type="radio"/>
50Hz	<input checked="" type="radio"/>
60Hz	<input type="radio"/>
1 Phase	<input checked="" type="radio"/>
kW per 24 hr (R290a)	<b>2.8</b>
kW per 24 hr (R134a)	<b>3.3</b>
Test Standard	<b>EN441</b>
Source	<b>ECA test</b>
Watts	<input type="radio"/>
Fuse Required	<b>13 amp</b>

### Product Extras

---

Helicoil Mains Lead	<input type="radio"/>
Door Pull Handle	<input type="radio"/>
Marine Kit	<input type="radio"/>

### Foot Notes

---

- Marine kit option includes legs, bulkhead brackets, rat proofing & marine shelves.
- Castors not available if product supplied less condensing unit

- 150mm must be kept above the top of the cabinet to allow for adequate airflow.
- Depth with door open is 1500mm
- Decibel rating measured 1m high from the floor and 1m out from the cabinet.

## Contact

---

### Foster Refrigerator

Oldmedow Road  
King's Lynn  
Norfolk  
PE30 4JU  
United Kingdom

Telephone: **0843 216 8800**  
Facsimile: **0843 216 4700**

sales@foster-uk.com



**GUARANTEEING YOU THE GREENEST REFRIGERATION AVAILABLE**