



new

Commando Coldrooms

Our new Commando 40 Coldroom Range has been designed to minimise turnaround time from order to final installation. With products available ex-stock and installation completed in a few hours, disruption to your business will be kept to a minimum.

Perfect where space is at a premium - in pubs, colleges, small restaurants and takeaways. Even with limited space and budget, caterers can now benefit from the increased storage capacity of a coldroom.

Complete installation in a matter of hours minimising disruption to your operation. Just order the size you need, and our highly skilled Installation Engineers will construct your new Foster Coldroom on site - it couldn't be simpler.



features & benefits

- The Commando Packaged Coldroom comes as a complete kit
 - coldroom panels
 - panel mounted refrigeration system
 - shelving
 - installation kit
- The Foster Commando construction system utilises the tried and tested Fosterlok system, ensuring hygienic, secure fixing to all panels
- Integrated panel-mounted refrigeration system: no complicated installation required. The front panel of the Coldroom is supplied with the refrigeration system already installed and ready to go
- No drainage required, so installation of your Commando Coldroom couldn't be easier
- Single phase electrical supply on all models - no specialist electrical work required



microprocessor control with digital display ensures constant visibility of temperature, recessed to prevent damage



pre-fitted interior light as standard with a separate light switch for easy use



new heavy duty refrigeration system supplied ready installed into the front panel of the coldroom ensures even temperature in the coldroom

the range & specification

- Available in 15 different sizes: from 4m³ to 10m³ capacities
- Refrigerator (+1/+4°C) and Freezer (-18/-21°C) temperatures available
- Suitable for high ambient operation
- Overall height of only 2.1m
- White laminate finish to exterior and interior
- 75mm insulated floor for thermal efficiency
- Non-slip, rigidised galvanised floor as standard offers safety in use
- Lockable, right hand hinged door comes complete with internal safety release handle
- Left hand door hinging optional

shelving

- Heavy duty 4 tier nylon wire to maximise the available storage space - 275kg loading per shelf up to 1200mm long
- Shelf height adjustable in 25mm increments offering flexible storage capacity

remote heat extraction system



- Water-cooled, heat-removal system available
- Cost-effective, simple solution for removing heat from your coldroom out of the kitchen, important where heat build-up is an issue on site
- Simple installation, reduces installation and commissioning costs and minimises disruption
- Once operational, the system offers environmental benefits with lower running costs and noise levels

Please see the Commando tech spec on page 62 to see the range of 40 Commando Coldroom Models























tamper-proof, hard-wearing door handle, door hinges and hardware pre-fitted for easy installation



hinged unit cover on the refrigeration system ensures easy access on site for servicing

Choose from our range of 20 Commando Coldroom models. Refrigerator and Freezer temps with Floors available in all configurations. Floorless models available in refrigerator temperature.

1812	1815	1818	2121
			
2112	2115	2118	2118N
			
2412	2415	2418	2418N
			
2712	2715	2718	2718N
			
3012	3015	3018	3018N
			

Overall height 2100mm on all models
Please allow 150mm to overall depth to allow for refrigeration system and door

All dimensions in mm

R404a as standard on all models.

PRV (pressure relief valve) supplied as standard on all models.

The standard position for the refrigeration system is on the left of the coldroom as shown above. Right hand mounting (with left hand door hinging) is an option to suit specific site conditions - please specify at the time of ordering.

Remote Heat Extraction System

Suitable for refrigerator and freezer temperatures.

Supplied with 30m of pipe for connection. Simple installation with the connection of two flexible pipes from unit to unit. Unit can be mounted up to 5 metres vertically away from the compressor and up to 25 metres horizontally.