

EPRO13L

Eco Pro 1/3 Freezer Counter




Temperature



Freezer
-18/-21 C

Dimensions (mm)

W 1865 D 700
H 865



Capacity

435 Litres

Features & Benefits

Providing excellence and practicality at a very competitive price, the Eco Pro range generates significant energy and carbon reductions in use saving you money on your operating costs whilst at the same time never compromising on your commitment to food safety

- High Quality 304 Stainless Steel Exterior Build Quality
- 60mm all-round insulation improves energy efficiency
- Fully floating lock provides durable security and prevents lock breakage if the key is left in
- Energy-saving Hydrocarbon refrigerant option at no extra cost
- Concealed refrigeration system maximises capacity with a tidy and practical interior

Supplied as Standard Optional Not Available Yes No

External Finish

304 Stainless Steel

304 Stainless Steel Rear For Island Siting

Internal Finish

304 Stainless Steel

Aluminium

Shelving

Additional Shelf

Nylon Coated Gastronorm 1/1 Shelf Quantity: 6

Nylon Coated Gastronorm 1/1 Basket

Worktop & Drawers

Worktop

100mm Splashback

Less Worktop

Doors

Solid Full

Base Fittings

80mm Castors

150mm Legs

Levelling Bolts

Refrigeration

| | |
|-----------------------------------|----------------------------------|
| Forced Air | <input checked="" type="radio"/> |
| Integral | <input checked="" type="radio"/> |
| Remote - less condensing unit | <input type="radio"/> |
| R290 (Hydrocarbon) | <input type="radio"/> |
| R404a | <input checked="" type="radio"/> |
| Thermal Heat Rejection (Kw/24hrs) | <input type="radio"/> |
| Noise DBA | <input type="radio"/> |
| Drain Required? | <input checked="" type="radio"/> |

Electrical Data

| | |
|----------------------|----------------------------------|
| 230 Volts | <input checked="" type="radio"/> |
| 50Hz | <input checked="" type="radio"/> |
| 60Hz | <input type="radio"/> |
| 1 Phase | <input checked="" type="radio"/> |
| kW per 24 hr (R404a) | 10.2 |
| Test Standard | PR EN153 |
| Source | Laboratory Test |
| Watts | <input type="radio"/> |
| Fuse Required | 13 amp |

Product Extras

| | |
|---------------------|-----------------------|
| Helicoil Mains Lead | <input type="radio"/> |
| Marine Kit | <input type="radio"/> |

Foot Notes

- Marine kit option includes legs, bulkhead brackets, rat proofing & marine shelves.
- Castors not available if product supplied less condensing unit
- 100mm leg option: height ranges from 835 to 865mm (replacement for standard castors). 150mm legs: height ranges from 885 to 935mm.

- Depth with door open is 1113mm
- Decibel rating measured 1m high from the floor and 1m out from the cabinet.
- 60Hz model supplied as 220v machine with separate transformer for conversion to 115v supply.

Contact

Foster Refrigerator

Oldmedow Road
 King's Lynn
 Norfolk
 PE30 4JU
 United Kingdom

Telephone: **0843 216 8800**
 Facsimile: **0843 216 4700**

sales@foster-uk.com



GUARANTEEING YOU THE GREENEST REFRIGERATION AVAILABLE