

# EPROG600H

## Eco Pro 600 Litre Upright Refrigerated Cabinet



### Temperature


---



Refrigerator  
1/4 C

### Dimensions (mm)

---



### Capacity

---

600 Litres

### Features & Benefits

---

Providing excellence and practicality at a very competitive price, the Eco Pro range generates significant energy and carbon reductions in use saving you money on your operating costs whilst at the same time never compromising on your commitment to food safety

- New, highly efficient, advanced ECM fans and clever circuit design optimises the performance of the refrigeration system and improves air movement delivering much lower energy consumption whilst still delivering food safe temperature performance.
- ECA Scheme Approved - as ECA products are guaranteed to be energy efficient, money can be claimed back on your investment
- Smart Controller reduces energy consumption by up to 20%

- Energy-saving Hydrocarbon refrigerant option offers up to 15% saving on running costs
- Energy Efficient self closing doors with durable steel hinges

Supplied as Standard    
  Optional    
  Not Available    
  Yes    
  No

### External Finish

---

- 304 Stainless Steel
- Stainless Steel
- 304 Stainless Steel Rear For Island Siting

### Internal Finish

---

- 304 Stainless Steel
- Aluminium

### Shelving

---

- Nylon Coated Gastronorm 2/1 Shelf  Quantity: 3
- Additional Shelf

### Doors

---

- Solid Full
- Solid Half
- Hinged - Right Hand
- Hinged - Left Hand
- Pass Through
- Glass
- Glass with Lights

### Base Fittings

---

- 80mm Castors
- 150mm Legs

## Refrigeration

---

Forced Air	<input checked="" type="radio"/>
Integral	<input checked="" type="radio"/>
Remote - less condensing unit	<input type="radio"/>
R290 (Hydrocarbon)	<input type="radio"/>
R134a	<input checked="" type="radio"/>
Thermal Heat Rejection (Kw/24hrs)	<input type="radio"/>
Noise DBA	<input type="radio"/>
Drain Required?	<input checked="" type="radio"/>

## Electrical Data

---

230 Volts	<input checked="" type="radio"/>
50Hz	<input checked="" type="radio"/>
60Hz	<input type="radio"/>
1 Phase	<input checked="" type="radio"/>
kW per 24 hr (R290a)	<b>1.9</b>
kW per 24 hr (R134a)	<b>1.86</b>
Test Standard	<b>EN441</b>
Source	<b>ECA test</b>
Watts	<input type="radio"/>
Fuse Required	<b>13 amp</b>

## Product Extras

---

Helicoil Mains Lead	<input type="radio"/>
Door Pull Handle	<input type="radio"/>
Marine Kit	<input type="radio"/>

## Foot Notes

---

- Marine kit option includes legs, bulkhead brackets, rat proofing & marine shelves.

- Hydrocarbon option not available on glass door models
- 32°C ambient on glass door refrigerator model
- Castors not available if product supplied less condensing unit
- Adequate airflow must be kept above the top of cabinet: 150mm
- Depth with door open is 1500mm
- Decibel rating measured 1m high from the floor and 1m out from the cabinet.

## Contact

---

### Foster Refrigerator

Oldmedow Road  
King's Lynn  
Norfolk  
PE30 4JU  
United Kingdom

Telephone: **0843 216 8800**  
Facsimile: **0843 216 4700**

sales@foster-uk.com



This logo signifies that the associated product meets and exceeds best practice 'Quick Wins' specification according to Buying Solutions public sector purchasing standards.



**GUARANTEEING YOU THE GREENEST REFRIGERATION AVAILABLE**



Authorised User No. 00101